

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A device for cooling a fuel cell that adjusts a temperature of the fuel cell to a target set temperature by supplying a coolant, comprising:
~~electric~~an electric conductivity measuring means for measuring a sensor that
measures an electric conductivity of the coolant; and
~~temperature means for measuring a~~temperature sensor that measures a
temperature of the ~~coolant; and~~coolant; wherein
~~means for estimating the device estimates~~the electric conductivity at the target
set temperature based on the electric conductivity of the coolant, the temperature of the coolant, and a correlation between the temperature and the conductivity of the ~~coolant;~~
~~wherein~~coolant, and
based on a correlation between a parameter related to the temperature of the coolant and the electric conductivity of the coolant, when the electric conductivity at the target set temperature exceeds a target electric conductivity range, the parameter related to the temperature of the coolant is controlled so as to maintain the electric conductivity at the target set temperature within the target electric conductivity range.
2. (Original) The device for cooling a fuel cell according to claim 1, wherein the parameter related to the temperature of the coolant is at least one element selected from the group including the temperature of the coolant, a cooling degree of the coolant, a required output of the fuel cell, an operation state of the fuel cell, and an external air temperature.
3. (Previously Presented) The device for cooling a fuel cell according to claim 1, wherein the temperature of the coolant is controlled by changing at least one of the cooling degree of the coolant and the operation state of the fuel cell.

4. (Currently Amended) The device for cooling a fuel cell according to claim 1, further comprising ~~electric conductivity decreasing means for decreasing an electric conductivity decreasing device that decreases~~ the electric conductivity of the coolant, wherein the parameter related to the temperature of the coolant is controlled based on the decrease quantity of the electric conductivity with the electric conductivity decreasing ~~means device.~~

5. (Currently Amended) The device for cooling a fuel cell according to claim 1, ~~further comprising: means for decreasing wherein the device decreases~~ the target set temperature when the electric conductivity at the target set temperature exceeds the target electric conductivity range.

6. (Currently Amended) The device for cooling a fuel cell according to claim 5, ~~further comprising means for increasing wherein the device increases~~ the target set temperature within a range in which the electric conductivity at the target set temperature does not exceed the target electric conductivity range.

7. (Previously Presented) A method for cooling a fuel cell by which a temperature of the fuel cell is adjusted to a target set temperature by supplying a coolant, the method comprising the steps of:

measuring a electric conductivity of the coolant;

measuring a temperature of the coolant;

estimating the electric conductivity at the target set temperature based on the electric conductivity of the coolant, the temperature of the coolant, and a correlation of the temperature and electric conductivity of the coolant;

controlling a parameter related to the temperature of the coolant and the electric conductivity of the coolant when the electric conductivity at the target set temperature exceeds a target electric conductivity range, so as to maintain the electric conductivity at the

target set temperature within the target electric conductivity range; and

decreasing the target set temperature when the electric conductivity at the target set temperature exceeds the target electric conductivity range.

8. (Original) The method for cooling a fuel cell according to claim 7, further comprising a step of increasing the target set temperature within a range in which the electric conductivity at the target set temperature does not exceed the target electric conductivity range.

9. (Previously Presented) The device for cooling a fuel cell according to claim 2, wherein the temperature of the coolant is controlled by changing at least one of the cooling degree of the coolant and the operation state of the fuel cell.

10. (Currently Amended) The device for cooling a fuel cell according to claim 2, further comprising ~~electric~~-an electric conductivity decreasing ~~means for decreasing device~~ that decreases the electric conductivity of the coolant, wherein

the parameter related to the temperature of the coolant is controlled based on the decrease quantity of the electric conductivity with the electric conductivity decreasing ~~means device~~.

11. (Currently Amended) The device for cooling a fuel cell according to claim 3, further comprising ~~electric~~-an electric conductivity decreasing ~~means for decreasing device~~ that decreases the electric conductivity of the coolant, wherein

the parameter related to the temperature of the coolant is controlled based on the decrease quantity of the electric conductivity with the electric conductivity decreasing ~~means device~~.

12. (Currently Amended) The device for cooling a fuel cell according to claim 9, further comprising ~~electric~~-an electric conductivity decreasing ~~means for decreasing device~~ that decreases the electric conductivity of the coolant, wherein

the parameter related to the temperature of the coolant is controlled based on the decrease quantity of the electric conductivity with the electric conductivity decreasing means device.